



CLEANING

PROMOSOLV™ 70

SOLVENT FOR DEGREASING & DEWAXING
VAPOR PHASE (MONO-SOLVENT) PROCESS
EXCELLENT CLEANING PERFORMANCE & LOW HSE IMPACT

BENEFITS

PROMOSOLV 70 is developed as a drop-in replacement for trichlorethylene, NPB and other solvents with a high Health, Safety & Environmental impact. While reducing substantially the HSE impact, the degreasing power is at an equivalent level.

It is dedicated to remove heavy oils, greases, waxes, particles, fluorinated lubricants. Depending on the nature of polymerised materials, some varnishes, adhesives, inks & paints could also be removed. PROMOSOLV 70 is compatible with all metals, including very sensitive ones. It has also good compatibility with most plastics & elastomers, however it is necessary to validate before use. The very low surface tension allows to penetrate and clean very tight or difficult to access spaces.

PROMOSOLV 70 is formulated with safety in mind. Its composition gives excellent flammability suppression properties, which provides a very high stability when used in an equipment. Some products in the market may lose their flammability suppression compound due to evaporation when used in an equipment.

PROMOSOLV 70 is qualified and used by several actors in the aerospace industry (e.g. SAFRAN IN 1500B).

This product also exists in a recycled version (made from recycled solvent) under the name PROMOSOLV 70 T

PERFORMANCE	<ul style="list-style-type: none"> Thermally and chemically stable in use The very low surface tension allows deep rinsing of parts with complex geometry Short cleaning, rinsing and drying times
COST	<ul style="list-style-type: none"> Continuous recycling in equipment for a long bath-life Can be returned for recycling and re-use The relative high boiling point reduces risk of solvent drag, so limiting consumption
HSE	<ul style="list-style-type: none"> Very low toxicity (refer to the SDS) No Ozon Depletion Potential (ODP) & low Global Warming Potential (GWP) Non-flammable

SPECIFICATIONS

SPECIFICATIONS	VALUES	METHODS
Aspect	Transparent, colorless	Visual
Methoxy-nonafluorobutane ether	30,0% ± 1,0	Internal / MO.SB.10033
1,2- Transdichloroethylene	70,0% ± 1,0	Internal / MO.SB.10033

CHARACTERISTICS

CHARACTERISTICS	VALUES
Boiling point (°C)	43
Vapor pressure (kPa)	65
Flash point	None
Density (g/cm ³)	1,28
Purity (% weight)	>99.0
Surface tension (dynes/cm)	14
Dynamic viscosity (mPa.s)	0.50
GWP	96

PROCESS RECOMMENDATION

The best process will depend on factors such as operating conditions, equipment, desired cleaning time and the nature of contaminants. Our team is ready to advise you.

PROCESS EXAMPLE



- Do not remove parts too quick out of the drying zone to prevent unwanted loss of solvent.
- Compatibility report of PROMOSOLV 70 with different materials is available on request.

PACKAGING, STORAGE & SHELF LIFE

- Keep products in closed original packaging and store at room temperature.
- Shelf life is minimum 18 months from production date when kept in recommended conditions.
- PROMOSOLV 70 is a like-azeotropic formulation which guarantees a safe use & storage.

AVAILABLE PACKAGING



255 Kg DRUM



35 Kg DRUM

HEALTH, SAFETY & ENVIRONMENT

Contains no Reach Substances (on Candidate list, Annex XIV & XVII) / Contains no persistent organic pollutant (EC 850/2004) / Contains no Import/Export Hazardous substances (EU 649/ 2012)

Used polluted product can be returned to us for recycling if regulations permit. Please contact your local sales contact for more details on our ECOPROGRAM.

Please refer always to the Safety Data Sheet (SDS or MSDS) prior to use. Our SDS can be downloaded at www.quickfds.com. We will request to provide your email address, so we can automatically send you a new version of the SDS when a future update would occur.

TECHNICAL SUPPORT & FREE-OF-CHARGE TESTING

Inventec has a worldwide dedicated Technical Support team to help you along the different stages of our cooperation.

Depending on your request, we provide online or onsite support

- to select the right product based on your specific needs
- to assist you in your product qualification process
- to guide you with the initial set up of you process at all your worldwide manufacturing facilities
- to provide fast response on technical issues which could occur at any time during mass production.

Customers are also welcome in our CLEANING CENTERS to see the process in action and to get convinced by our solutions. We cover water- and solvent based processes.

Inventec is unique in the world by developing not only cleaning materials but also soldering and coating solutions. These materials are very closely linked with each other from a process point of view. Talking to our Technical Team, who understands very well these 3 different product groups, will help you greatly to overcome technical challenges within your overall process.

Contact our technical support via contact@inventec.dehon.com or your local sales representative.

ABOUT INVENTEC

Inventec is a global provider of CLEANING, SOLDERING & COATING materials for Electronic, Semiconductor and Industrial applications. For over 40 years we have shown leadership in innovation by putting HEALTH IMPACT, SUSTAINABILITY and RELIABILITY at the core of our product development.

With ISO 9001 & 14001 production sites in France, Switzerland, USA, Mexico, Malaysia and China we can guarantee a smooth and cost-effective supply chain.

We supply to many industries but the excellent performance of our products in applications which demand high reliability, leads us to focus especially on the AUTOMOTIVE, AEROSPACE, SEMICONDUCTOR, ENERGY and MEDICAL industry.

www.inventec.dehon.com



S O L D E R I N G • C L E A N I N G • C O A T I N G

In accordance with the Annex II of Directive 2011/65/UE (RoHS), including its amendments, we certify that this product does not contains quantities above 0.1% of Hg, Pb, Cr VI, PBB, PBDE, DEHP, BBP, DBP, DIBP and above 0.01% of Cd

This data is based on information that the manufacturer believes to be reliable and offered in good faith. In no event will INVENTEC PERFORMANCE CHEMICALS be responsible for special, incidental and consequential damages. The user is responsible to the Administrative Authorities (regulations for the protection of the Environment) for the conformity of his installation.

Inventec Performance Chemicals – 26 rue de Coulons. 94360 Bry-sur-Marne, France
Limited company with capital of 600 000€ - 964 500 706 RCS Créteil