

TOPKLEAN[™] MC 20A

HYDROCARBON OIL & GREASE REMOVAL CO-SOLVENT PROCESS SUSTAINABLE ALTERNATIVE TO PERCHLORETHYLENE & nPB

BENEFITS

TOPKLEAN MC 20A is especially designed to remove hydrocarbon oils & greases from all metals and most plastics. It could also remove a small quantity of water-soluble oils and minerals but need to be evaluated & tested before. It brings a shiny effect on sensitive alloys & metals.

It is used in co-solvent process to offer a fast & sustainable cleaning process in accordance with the latest and future environmental regulations with very high cleaning efficiency. It is the only solvent process which can reach even better cleaning efficiency levels (kb values) than nPB, perchloroethylene and other hazardous alternatives.

In a Co-solvent process, TOPKLEAN MC 20A is rinsed perfectly with Hydrofluoroethers (HFE) based rinsing fluids from 3MTM NovecTM or our own PROMOSOLVTM range. Thanks to the very low surface tension of HFE, the rinsing will penetrate into the very tight or difficult to reach spaces. It will dissolve any remaining contaminations, resulting in very low contamination levels. Besides, compared with a water based cleaning system, there is no risk of corrosion due to the absence of residual water left on the parts.

TOPKLEAN MC 20A together with the co-solvent process has been a game changer for over 15 years now and is qualified and used by several actors in the automotive, aerospace and micromechanics industry.

PERFORMANCE	 Excellent solubility of hydrocarbon oils & greases Excellent compatibility with all metals, glasses, ceramic & many plastics Perfect cleaning, even in tight spaces and under low stand-off components Allows shining effect to sensitive alloys & metals
соѕт	 Fast process allows increase in production capacity Rinsing fluid is constantly recycled, limiting consumption. No water consumption & no need for wastewater treatment
HSE	 Low toxicity (refer to the SDS) No Ozon Depletion Potential (ODP) & no Global Warming Potential (GWP) High flash point - safe to use, storage & transport No aromatics & halogenated compounds

SPECIFICATIONS

SPECIFICATIONS	VALUES	METHODS
Aspect	Transparent, colorless	Visual
Density at 20°C (g/ml)	0.790 ± 0.010	BRY MO 028

CHARACTERISTICS

CHARACTERISTICS	VALUES	METHODS
Boiling point (°C / °F)	170-180 °C /	ASTM D1078
Flash Point (PMCC)	65°C / 149°F	ASTM D93
Viscosity at 25°C	1,6mm²/s	ASTM D445
Surface tension at 20°C (dynes/cm)	41	ASTM D971
Relative evaporation rate : nBuAc=1	0,06	ASTM D3539
Dielectric rigidity	200 KV/cm	DIN/VDE 0370/5
Miscibility in water	Not miscible	Internal
Relative Vapor density at 20°C	4,6	Internal
Latent heat of vaporization (kJ/kg at bp)	320	Calculated
Specific heat (kJ/kg.K)	2.0/2.1	Calculated
Heat conductivity at 20°C	0,13 W/M.K	Calculated
Presence of aromatic compounds (% weight)	<0.01 %	SMS 2728
NVR (G/100 mL)	<0,01	ASTM D1353
Water content (% weight)	<0.1	ASTM E1364
Boiling range (°C / °K)	174-199 °C / 345-390 °F	ASTM D1078
VOC	776 g/L	

PROCESS RECOMMENDATION

The best process will depend on factors such as operating conditions, equipment, desired cleaning time and the nature of contaminants. Our team is ready to advise you.

PROCESS EXAMPLE

Mixed co-solvent process for HC oil & grease removal

TOPKLEAN MC 20A (70%) PROMOSOLV DR1 (30%)	PROMOSOLV DR1	PROMOSOLV DR1 Vapor phase
Conc: mix 70/30 % vol Temp: 65-72 °C / 149-162 °F US: yes Time: 5-10 min	Conc: 100% Temp: 45°C /113 °F US: optional Time: 2-5 min	Conc : 100% DR1 vapor Temp : 55°C / 130 °F Time: 5- 60 sec
CLEANING	RINSING	DRYING
Separated co-solvent process	for HC oil & grease removal	
TOPKLEAN MC 20A	PROMOSOLV DR1	PROMOSOLV DR1

TOPKLEAN MC 20A	PROMOSOLV DR1	PROMOSOLV DR1	Vapor phase
Conc: 100 % Temp: 47 °C / 116 °F US: Yes Time: 5-10 min	Conc: 100% Temp: 55 °C / 130 °F US: optional Time: 2-5 min	Conc: 100% Temp: 45°C /113 °F US: optional Time: 2-5 min	Conc : 100% DR1 vapor Temp : 55°C / 130 °F Time: 5- 60 sec
CLEANING	RINSING	RINSING	DRYING

• A dedicated PCA Kit to monitor the bath status and compatibility report of TOPKLEAN MC 20A with different materials are available on request.



PACKAGING, STORAGE & SHELF LIFE

- Keep products in closed original packaging and store at room temperature.
- Shelf life is minimum 18 months from production date when kept in recommended conditions.



20 L CANISTER 200 L DRUM

HEALTH, SAFETY & ENVIRONMENT

TOPKLEAN MC 20A is NOT a CREENWAY product. Although fully in line with safety & environmental regulations, this product doesn't match our strict criteria to be labelled as a Greenway product.

More info on our Greenway concept via this link



LOOKING FOR A MORE SUSTAINABLE SOLUTION?

GREENWAY ALTERNATIVE

We currently don't have a Greenway alternative but our target is to develop one in the near future. In case you want us to prioritize the development of a Greenway alternative, do not hesitate to contact us.

Contains no Reach Substances (on Candidate list, Annex XIV & XVII) / Contains no persistent organic pollutant (EC 850/2004) / Contains no Import/Export Hazardous substances (EU 649/ 2012)

Please refer always to the Safety Data Sheet (SDS or MSDS) prior to use. Our SDS can be downloaded at www.quickfds.com. We will request to provide your email address, so we can automatically send you a new version of the SDS when a future update would occur.

TECHNICAL SUPPORT & FREE-OF-CHARGE TESTING

Inventec has a worldwide dedicated Technical Support team to help you along the different stages of our cooperation.

Depending on your request, we provide online or onsite support

- to select the right product based on your specific needs
- to assist you in your product qualification process
- to guide you with the initial set up of you process at all your worldwide manufacturing facilities
- to provide fast response on technical issues which could occur at any time during mass production.

Customers are also welcome in our CLEANING CENTERS to see the process in action and to get convinced by our solutions. We cover water- and solvent based processes.

Inventec is unique in the world by developing not only cleaning materials but also soldering and coating solutions. These materials are very closely linked with each other from a process point of view. Talking to our Technical Team, who understands very well these 3 different product groups, will help you greatly to overcome technical challenges within your overall process.

Contact our technical support via contact@inventec.dehon.com or your local sales representative.



ABOUT INVENTEC

Inventec is a global provider of CLEANING, SOLDERING & COATING materials for Electronic, Semiconductor and Industrial applications. For over 40 years we have shown leadership in innovation by putting HEALTH IMPACT, SUSTAINABILITY and RELIABILITY at the core of our product development.

With ISO 9001 & 14001 production sites in France, Switzerland, USA, Mexico, Malaysia and China we can guarantee a smooth and cost-effective supply chain.

We supply to many industries but the excellent performance of our products in applications which demand high reliability, leads us to focus especially on the AUTOMOTIVE, AEROSPACE, SEMICONDUCTOR, ENERGY and MEDICAL industry.

www.inventec.dehon.com



SOLDERING • CLEANING • COATING

In accordance with the Annex II of Directive 2011/65/UE (RoHS), including its amendments, we certify that this product does not contains quantities above 0.1% of Hg, Pb, Cr VI, PBB, PBDE, DEHP, BBP, DBP, DIBP and above 0.01% of Cd

This data is based on information that the manufacturer believes to be reliable and offered in good faith. In no event will INVENTEC PERFORMANCE CHEMICALS be responsible for special, incidental and consequential damages. The user is responsible to the Administrative Authorities (regulations for the protection of the Environment) for the conformity of his installation.

Inventec Performance Chemicals – 26 rue de Coulons. 94360 Bry-sur-Marne, France Limited company with capital of 600 000€ - 964 500 706 RCS Créteil

